

CAT.5E F/UTP PATCH CORD - CA5EFxxM00L



Browse on Mobile

 Browse on Web

NEXCONEC[®] Category 5E F/UTP patch cords are specifically designed and manufactured to deliver robust standards-based performance ensuring optimum bandwidth for today's high-speed network applications. The patch cord is double shielded which is ideal use in external interference environment.

Each Category 5E F/UTP patch cord exceed the minimum specified performance for Category 5E F/UTP patch cords and support all CLASS D applications.

FEATURES

- ✓ Conform to IEC, EIA-TIA performance requirements
- ✓ Gold plated contact pins
- ✓ 26AWG premium grade copper conductor
- ✓ Snag-less Connectors

APPLICATIONS

- ✓ Supports category 5E (Class D) networks running up to 100MHz applications
- ✓ Ideal for environments where external interferences can disrupt signals
- ✓ Connection between wall outlets or equipment's

SPECIFICATIONS

Parameters	Units	Value
Cable OD	mm	5.3 ±0.2mm
Conductor		26AWG stranded copper
Insulators Diameter	mm	0.97±0.05mm
Insulators Material		HDPE
Shielding		Aluminum foil for overall four pairs
Aluminum Foil		125% coverage
Termination Wiring		TIA-568B *other wiring method on request
Operating Temperature	°C	-10°C / +60°C
Compliance		ANSI/TIA-568-C.2, ISO 11801, IEC 60603-7
RoHS Compliance		Compliant
Warranty		12 Months

ORDER INFORMATION

Part Number	Product Description
CA5EFxxM00L	NEXCONEC CAT5E F/UTP Patch Cord xx 00mtr LSZH
CA5EFxxM00C	NEXCONEC CAT5E F/UTP Patch Cord xx 00mtr CM
CA5EFxxM00P	NEXCONEC CAT5E F/UTP Patch Cord xx 00mtr PVC

Note:

1. "xx" is the jacket color, refer to table below

xx	color
GY	Grey
BL	Blue
BK	Black
GR	Green
YE	Yellow
PR	Purple
RD	Red

2. "00" is the length of patch cord, i.e.: 0.5 for 0.5mtr; 01 for 1mtr; 02 for 2mtr.

3. Contact NEXCONEC sales for more information now.