

CAT.5E STP MINI SHUTTERED KEYSTONE JACKS - CN5ESTME/MS









NEXCONEC® Category 5E shielded tool free RJ-45 keystone jacks exceed the transmission line performance requirements of IEC and TIA for CLASS-D/Category 5E systems. Their compact design has been engineered to optimize density in high performance applications such as Data Centers. Each Cat 5E shielded RJ-45 keystone jacks comply with IEC 60603-7-3 (Shielded) and support all applications designed for CLASS-D networks, as defined within ISO/IEC 11801 (2nd Edition): 2010 including ATM-155, 100BASE-Tx, Token Ring 100Mbs-1, and 1G FCBASE-T.

With its shuttered design which offers the dust free and well protection to the contact pins inside Keystone jack.

FEATURES

- Easy and fast tool free termination
- Fits all keystone style face plates and floor boxes
- Suitable for modular screened patch panel installation

APPLICATIONS

- Support Class-D/category 5E standards networks
- Independent third party verified performance
- Terminates 23AWG to 26AWG cables



SPECIFICATIONS

Parameters	Value	
Shell Material	Zinc Die-Casting and Nickel plating	
Plastic Parts	High quality engineering plastic	
Jack Wire	Stamp Pin 0.35mm, Phosphor Bronze Gold over Nickel Plating	
IDC Conductor	0.5mm Phosphor Bronze, Tin-plating	
Jack Contact Life	Min. 750 Insertions	
Contact Compatibility	Accommodate 23 to 26 AWG Solid	
Wiring Block Life	Min. 200 term. cycles	
РСВ	FR-4, 1.2mm Thickness	
Termination	180° Termination	
Termination Wiring	TIA-568A or TIA-568B	
TIA Cat.5E Perm. Link Test	Worst Pair NEXT Headroom ≥5.0dB	
Operating Temperature	-10°C / +60°C	
Operating Humidity	10% ~ 90% RH	
Storage Temperature	-40°C ~ +68°C	
Compliance	ANSI/TIA-568.2-D-2018, ISO/IEC 11801-1-2017, YDT926.3-2009, ISO/IEC 60603-7-3	
RoHS	Compliant	
Warranty	12 Months	
Packing	25pcs per carton	

ORDER INFORMATION

Product	Part Number	Product Description
	CN5ESTME/MS	NEXCONEC Keystone Jack Cat.5e Shielded, with Shutter



TECHNICAL DRAWING







