

CAT.5E UTP KEYSTONE JACKS - CN5EUTBK









NEXCONEC® Category 5e tool free RJ-45 keystone jacks exceed the transmission line performance requirements of IEC and TIA for CLASS D/Category 5e systems. Each Category 5e tool free RJ-45 keystone jacks comply with IEC 60603-7-2 (Unshielded) and support all applications designed for CLASS-D networks, as defined within ISO/IEC 11801 (2nd Edition): 2010 including ATM-155, 100BASE-Tx, Token Ring 100Mbs-1, and 1G FCBASE-T.

FEATURES

- Easy and fast tool free termination
- Fits all keystone style face plates and floor boxes
- Suitable for modular screened patch panel installation

APPLICATIONS

- Support Class-D/Category 5E standards networks
- Independent third party verified performance
- Terminates 23AWG to 26AWG cables



SPECIFICATIONS

Parameters	Value
Shell Material	High impact flame retardant plastic, PC UL 94V-0
РСВ	FR-4, 1.2mm Thickness
Jack Wire	Stamp Pin 0.35mm, Phosphor Bronze Gold over Nickel Plating
IDC Conductor	0.5mm Phosphor Bronze, Tin-plating
Contact Compatibility	Accommodates 23 to 26AWG Solid Copper
Jack Contact Life	Min. 750 Insertions
Wiring Block Life	Min. 200 term. cycles
Termination	180° Termination
Termination Wiring	TIA-568A or TIA-568B
Storage Temperature	-40 ~ +68 °C
Operating Temperature	-10 ~ +60 °C
Operating Humidity	10% ~ 90% RH
Standards & Compliance	ANSI/TIA-568-C.2, ISO 11801, IEC 60603-7-2, ETL Verified
RoHS	Compliant
Warranty	12 Months
Packing	25pcs per carton

ORDER INFORMATION

Product	Part Number	Product Description	
A CALLS	CN5EUTBK	NEXCONEC CAT.5E UTP Keystone Jack (Black) Tool less	






CN5EUTWH

NEXCONEC CAT.5E UTP Keystone Jack (White) Tool less

TECHNICAL DRAWING



^{*} Other colors available on request