

CAT.6 UTP MINI KEYSTONE JACKS - CN6UTBK/M









NEXCONEC® Category 6 tool free RJ-45 Mini keystone jacks exceed the transmission line performance requirements of IEC and TIA for CLASS E/Category 6 systems. Each Category 6 tool free RJ-45 MINI keystone jacks comply with IEC 60603-7-4 (unshielded) and support all applications designed for CLASS E networks, as defined within ISO/IEC 11801 (2nd Edition): 2010 including ATM-1200, 1000BASET (Gigabit Ethernet), and 1G FCBASE-T.

FEATURES

- Easy and fast tool free termination
- Fits all keystone style face plates and floor boxes
- Shorter length for better cable routing inside backbox with faceplate
- Suitable for modular unscreened patch panel installation
- Support application with PoE, IEEE 802.3bt PoE++ Type 4

APPLICATIONS

- Support Class-E/Category 6 standards networks
- Independent third party verified performance
- Terminates 23AWG to 26AWG conductors



SPECIFICATIONS

Parameters	Value
Shell Material	High quality engineering plastic
Jack Wire	Stamp Pin 0.35mm, Phosphor Bronze Gold over Nickel Plating
IDC Conductor	0.5mm Phosphor Bronze, Tin-plating
Jack Contact Life	Min. 750 Insertions
Contact Compatibility	Accommodate 22 to 24 AWG Solid
Wiring Block Life	Min. 200 term. cycles
PCB	FR-4, 1.2mm Thickness
Termination	180° Termination
Termination Wiring	TIA-568A or TIA-568B
TIA Cat.6 Perm. Link Test	Worst Pair NEXT Headroom ≥3.0dB
Operating Temperature	-10°C / +60°C
Operating Humidity	10% ~ 90% RH
Storage Temperature	-40°C ~ +68°C
Application	Support application with PoE, IEEE 802.3bt PoE++ Type 4
Compliance	ANSI/TIA-568-C.2, ISO 11801, IEC 60603-7
RoHS	Compliant
Warranty	12 Months
Packing	25pcs per bag

ORDER INFORMATION

Part Number	Product Description
CN6UTBK/M	NEXCONEC CAT.6 UTP Mini Keystone Jack Tool less, Black
CN6UTWH/M	NEXCONEC CAT.6 UTP Mini Keystone Jack Tool less, White



TECHNICAL DRAWING



