

## DEAD ZONE ELIMINATOR



Browse on Mobile

 Browse on Web

The NEXCONEC<sup>®</sup> Dead Zone Eliminator establishes a connection with the OTDR and the link that is being tested, with the aim of evaluating the link's attenuation and the reflectance of the connection at the near end. This dead zone is provided in a robust, compact plastic casing, ideal for use in a rugged environment.

### FEATURES

- ✓ Conform to IEC, EIA-TIA and Telecordia performance requirements
- ✓ Available in standard Single mode and Multimode fiber options
- ✓ Available with different connector types
- ✓ Available in compact IP rated casing, watertight, Dust-proof and impact proof
- ✓ Stainless steel components

### APPLICATIONS

- ✓ Telecommunication networks
- ✓ Data centers
- ✓ FTTx

## SPECIFICATIONS

Parameters	Value
Dimensions (WxHxD)	135 x 240 x 65 mm
Fiber Length	Max 2000m
Tail Length	2m
Connector Type	SC/LC/FC/ST
Weight	650 gm

## ORDER INFORMATION

AP	-	1	2	3	4	-	DIST
----	---	---	---	---	---	---	------

1	2	CONNECTOR	3	FIBER		TAIL LENGTH
S1	S1	SC	D2	G652D	2	2M
L1	L1	LC	A1	G657A1		
F1	F1	FC	O1	OM1		
T1	T1	ST	O2	OM2		
			O3	OM3		
			O4	OM4		

\*\*\* Fiber Length or Distance are based on Fiber Types