

## DOME ENCLOSURE - **OC-DO05**



Browse on Mobile

 [Browse on Web](#)

NEXCONEC Dome closure is the best designed and innovative solution for fiber cabling installation. It adopts fully mechanical sealing structure for good sealing performance of fiber cable over 240fibers. The different sizes of cable entrances provide the great flexibility for cables installation.

### FEATURES AND APPLICATIONS

- ✓ Higher density
- ✓ Adequate space for fibers storage
- ✓ Easy operation
- ✓ Single Core or Mass Fusion splice

## SPECIFICATIONS

Parameters	Value
Dimensions (HxD)	455 x 220 mm
Weight (Kg)	3.3 - 4.2 Kg
Splice Tray Capacity	24 fibers
Max Number of Trays	10 pcs
Max. Capacity (Fibers)	240 fibers
Number of Inlet/Outlet Ports	6
Diameter of Fiber Cable	Φ8mm - Φ21mm
Sealing Structure	Mechanical
Sealing Rating	IP68
Operating Temperature	-40°C ~ 65°C
Impact Strength	16 N.m / IK09

## ORDER INFORMATION

Part Number	Product Description
<b>OC-DO05-24</b>	FO Dome Enclosure 24FO MEC
<b>OC-DO05-48</b>	FO Dome Enclosure 48FO MEC
<b>OC-DO05-72</b>	FO Dome Enclosure 72FO MEC
<b>OC-DO05-96</b>	FO Dome Enclosure 96FO MEC
<b>OC-DO05-144</b>	FO Dome Enclosure 144FO MEC
<b>OC-DO05-168</b>	FO Dome Enclosure 168FO MEC
<b>OC-DO05-192</b>	FO Dome Enclosure 192FO MEC
<b>OC-DO05-216</b>	FO Dome Enclosure 216FO MEC
<b>OC-DO05-240</b>	FO Dome Enclosure 240FO MEC