

FTTH SUBSCRIBER WALL OUTLET - **WO01/02**



Browse on Mobile

 [Browse on Web](#)

The compact termination box supplied by NEXCONEC[®] is designed for use in residential and business applications for the termination of up to four fibers. This wall box enables the installation of either a single Sirocco Blown Tube cable using up to a 2 fiber blown unit or two 2 fiber ruggedized cables to be spliced to 2 SC pigtails (PC or APC), which connect to adapters at the base of the unit.

This box is supplied with a transparent plastic cover on the front adaptor side, providing major protection to the installed fibers.

FEATURES

- ✓ SC Simplex / LC Duplex Adapter type
- ✓ Ergonomic Design
- ✓ Flip tray to allow access to pigtails and Cable entry
- ✓ Removable cover for easy access
- ✓ Unit manufactured with fire resistant UL94-V0 Rated Material
- ✓ Transparent lid cover for shutter

APPLICATIONS

- ✓ FTTH / FTTx Networks
- ✓ Data communication Networks
- ✓ Indoor Application

SPECIFICATIONS

Parameters	Value
Width	85 mm
Height	23 mm
Depth	116 mm
Number of Ports	1
Max. Splicing Capacity	2 Splices
Suitable Adapter Type	SC Simplex – SC Duplex
Material	PC + ABS
Operating Temperature	-40 °C ~ +50°C
Color	White
Compliant to	RoHS, REACH, SVHC

ORDER INFORMATION

Part Number	Product Description
WO01	Subscriber Wall Outlet 1 Port SC Simplex Unloaded
WO02	Subscriber Wall Outlet 1 Port SC Duplex Unloaded