

## DOME ENCLOSURE - **OC-DO06**



Browse on Mobile



Browse on Web

NEXCONEC<sup>®</sup> Compact Dome closure with a hinged door for easy access and maintenance is an innovative solution to manage up to 60 fibers. The enclosure is ruggedized for harsh environment with IP68 rating. Multiple installation application for FTTH with wall mount and aerial. The different sizes of cable entrances provide the great flexibility for cables installation.

### FEATURES AND APPLICATIONS

- ✓ Compact with integrated fiber management
- ✓ Outdoor IP68 Rated
- ✓ Easy operation with hinged door
- ✓ Mechanical sealing with multiple cable entry points

## SPECIFICATIONS

| Parameters                   | Value                  |
|------------------------------|------------------------|
| Dimensions (HxWxD)           | 300 x 220 x 100 mm     |
| Weight (Kg)                  | 2.4 - 2.7 Kg           |
| Material                     | ABS                    |
| Splice Tray Capacity         | 12 fibers              |
| Max Number of Trays          | 5 pcs                  |
| Max. Capacity (Fibers)       | 60 fibers              |
| Number of Inlet/Outlet Ports | 3                      |
| Suitable Fiber Cable OD      | Φ8mm – Φ15mm           |
| Number of Φ2mm Entries       | 4                      |
| Sealing Structure            | Mechanical Compression |
| Sealing Rating               | IP68                   |
| Operating Temperature        | -40°C ~ +65°C          |
| Impact Strength              | 10 N.m / IK08          |

## ORDER INFORMATION

| Part Number         | Product Description           |
|---------------------|-------------------------------|
| <b>OC-DO06-12</b>   | FO Dome Enclosure 12FO Hinged |
| <b>OC-DO06-24</b>   | FO Dome Enclosure 24FO Hinged |
| <b>OC-DO06-36</b>   | FO Dome Enclosure 36FO Hinged |
| <b>OC-DO06-48</b>   | FO Dome Enclosure 48FO Hinged |
| <b>OC-DO06-60</b>   | FO Dome Enclosure 60FO Hinged |
| <b>OC-DO06-POLE</b> | Pole Mounting Kit for OC-DO06 |