

## LOCKABLE INDOOR/OUTDOOR WALL BOX 24 PORTS SC - WP24U1



Browse on Mobile

 [Browse on Web](#)

NEXCONEC<sup>®</sup> Lockable IP65 & UV Resistant distribution box is supplied unloaded as standard and offers the ability to terminate 24 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications.

An internal detachable tray provides a neat and tidy solution for housing 24 SC simplex connections and splices. The box has 24 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating.

### FEATURES

- ✓ Up to 24 splice with SC Simplex Adapter
- ✓ Lockable Door for security
- ✓ IP65 & UV Resistant
- ✓ Accepts loose tube, distribution and pre-terminated cables
- ✓ Removable splice tray for easy installation
- ✓ Integrated bend radius protection
- ✓ ROHS, REACH & SVHC compliant

### APPLICATIONS

- ✓ FTTH / FTTx Networks
- ✓ Data communication Networks
- ✓ Indoor/Outdoor Application

## SPECIFICATIONS

Parameters	Value
Width	270 mm
Height	340 mm
Depth	110 mm
Number of Ports	24 SC Simplex
Number of Cables Entry	<b>Left:</b> 2x Ports (for 8.5 to 13mm OD) <b>Middle:</b> 2x Optional Uncut Round Ports, with 20mm diameter, to load PG13.5 Gland for cables OD 6mm to 10mm
Number of Cables Exit	<b>Right:</b> 24x Ports (for 2x3mm FTTH Flat Drop Cables)
Max. Splicing Capacity	24 Splices
Material	ABS
Color	Grey RAL7035
Net Weight (Kg)	1.8 Kg
Operating Temperature	-40 °C ~ +60°C
Compliant to	RoHS, REACH, SVHC

## ORDER INFORMATION

Part Number	Product Description
<b>WP24U1</b>	In/Out Lockable Wall Box IP65 UV Resistant 24 Positions SC Simplex Unloaded