

MTP[®]/MPO CONVERSION TRUNKS **1x(BASE-16)** to **2x(BASE-8)**




Browse on Mobile

 [Browse on Web](#)

The NEXCONEC[®] MTP[®]/MPO Conversion Trunk Cables are compact, high-density fiber connector assemblies designed for use in high-density environments. Unlike MTP[®]/MPO Trunk cables, MTP[®]/MPO conversion trunk cables are terminated with MTP[®]/MPO connectors on both ends and can provide more possibilities for the existing 16-fiber cabling system.

These trunks are ideal for connecting equipment or interconnecting modules/panels in data center applications up to 400G, linking two InfiniBand 200G QSFP56 or optical QSFP56 transceivers transmission to 400G QSFP-DD or optical QSFP-DD/OSFP transceiver transmission. Our MTP[®]/MPO connectors come in both Standard and Elite versions to accommodate the varying power budget needs of our customers.

FEATURES


- ✓ Conform to IEC, EIA-TIA, and Telcordia performance requirements
- ✓ All Assemblies are machine polished providing highest quality
- ✓ Cable terminated with **1x (base-16) & 2x (base-8)** fiber MTP[®]/MPO Connectors
- ✓ Optional MPO push/pull release boot
- ✓ Available in custom length and cable construction is 16 fibers
- ✓ All Assemblies are factory tested and come with test certificate
- ✓ Factory pre-terminated assemblies with protocol for constant and reliable quality
- ✓ CPR Euro classes certified on demand 

APPLICATIONS

- ✓ Telecommunication networks
- ✓ Data centers, Co-location DC
- ✓ LAN or Campus wide Network
- ✓ Supports up to 400G applications



16 Fiber MTP/MPO



8 Fiber MTP/MPO

MTP[®]/MPO CONNECTOR SPECIFICATIONS

Parameters	IL – Max	IL – Typical	RL
SM – Standard	0.75 dB	0.40 dB	> 55 dB
SM – Premium	0.35 dB	0.20 dB	> 55 dB
MM – Standard	0.60 dB	0.40 dB	> 20 dB
MM – Premium	0.35 dB	0.20 dB	> 20 dB

*** For single mode premium grade is only available with Usconec MTP.

CABLE CHARACTERISTICS

Parameters	Units	Value
Fiber Count		16F
Number of Fibers per Tube		16
Number of Micro Tubes		1
Outer Diameter	mm	Double jacket 16F – 4.5
Tail Diameter	mm	3.0
Tensile Strength (Long Term)	N	150
Tensile Strength (Short Term)	N	400

Crush Resistance (Long Term)	N/100mm	300
Crush Resistance (Short Term)	N/100mm	1000
Min. Bending Radius	mm	10D (Static) / 20D (Dynamic)
Cable Jacket Material		LSZH or PVC
Strength Member		Kevlar, Aramid Yarn
Storage Temperature	°C	-20 ~ +70
Operating Temperature	°C	-20 ~ +70
Installation Temperature	°C	-10 ~ +50
Compliance		RoHS, REACH & SvHC
CPR Reaction to Fire Classification	Certified	Cca-s1a,d0,a1

ORDER INFORMATION

MO	1	2	3	4	5	6	7	8	DIST
----	---	---	---	---	---	---	---	---	------

MO	1	CONNECTOR	2	CONNECTOR	3	4	FIBER	5	CABLE CONSTRUCTION	6	JACKET COLOR	7	JACKET MATERIAL	8	POLARITY
K6	16F MPOF STD	G1	8F MPOF STD	16-144	2D	G652D	D	Micro Double	Y	YELLOW	L	LSZH	A	POL A	
K7	16F MPOM STD	G2	8F MPOM STD		A1	G657A1			O	ORANGE	R	OFNR	B	POL B	
K8	16F MPOF ELITE	G3	8F MPOF ELITE		A2	G657A2			Q	AQUA	P	OFNP	C	POL C	
K9	16F MPOM ELITE	G4	8F MPOM ELITE		O1	OM1			V	ERICA VIOLET	LC	LSZH Cca			
					O2	OM2			B	BLACK					
					O3	OM3			G	LIME GREEN					
					O4	OM4									
					O5	OM5									

*For MTP® from USCONEC, above PN must start with MT instead of MO.