

## 10G XFP TRANSCEIVER



Browse on Mobile



Browse on Web

Nexconec 10G XFP Transceivers support 8.5G and 10G CDR optional, 1550nm EML transmitter for ER and ZR, commercial and industrial operating temperature optional.

### FEATURES

- ✓ Up to 11.1Gbps Data Links
- ✓ Single +3.3V power supply, power dissipation < 1.5W
- ✓ Hot-pluggable
- ✓ Operating temperature range: Standard: 0 to +70°C, Industrial: -40 to +85°C
- ✓ RoHS Compliant
- ✓ Compliant with EMI,ESD
- ✓ Compliant with MSA SFP+ specification(SFF-8431), SFF-8472, SFP+ MSA, XFP MSA
- ✓ Compliant to IEEE 802.3ae

### APPLICATIONS

- ✓ 10GBASE-ZR/ZW, 10G Ethernet, SONET OC-192 &SDH STM 64

## SPECIFICATIONS

Part Number	Package	Data Rate	Wavelength	Reach	TX	RX	Connector	TX Power	RX Sensitivity
NX-XF-8G10-01-xx	XFP	10G	850nm	300m	VCSEL	PIN	LC	-6~-1dBm	-10dBm
NX-XF-3G10-01-xx	XFP	10G	1310nm	300m	FP	PIN	LC	-6~-1dBm	-15dBm
NX-XF-3G10-10-xx	XFP	10G	1310nm	10km	DFB	PIN	LC	-6~-1dBm	-15dBm
NX-XF-5G10-40-xx	XFP	10G	1550nm	40km	EML	PIN	LC	-1~4dBm	-16.5dBm
NX-XF-5G10-80-xx	XFP	10G	1550nm	80km	EML	APD	LC	0~5dBm	-24dBm

## ORDER INFORMATION

Part Number	Product Description
<b>NX-XF-8G10-01-xx</b>	10G XFP SR Transceiver LC Duplex, (850nm) MMF 300m
<b>NX-XF-3G10-01-xx</b>	10G XFP LRM Transceiver LC Duplex, (1310nm) SMF 300m
<b>NX-XF-3G10-10-xx</b>	10G XFP LR Transceiver LC Duplex, (1310nm) SMF 10km
<b>NX-XF-5G10-40-xx</b>	10G XFP ER Transceiver LC Duplex, (1550nm) SMF 40km
<b>NX-XF-5G10-80-xx</b>	10G XFP ZR Transceiver LC Duplex, (1550nm) SMF 80km

### Notes

- Where (01 = 300m, 10 = 10km etc.) denotes reach in kilometers.
- Where "xx" denotes compatibility short codes. (xx = CI for Cisco, xx = DL for DELL etc.)
- Compatible Short codes are as follows:

Short codes	Value	Short codes	Value
CI	Cisco	HW	Huawei
ML	Mellanox	DK	D-Link
MK	Mikrotik	HC	H3C
JP	Juniper	CN	Ciena
BR	Brocade	EC	Edge-Core
DL	DELL	AL	Alcatel-Lucent
FT	Fortinet		